HSR (LONDON),
HOUGHTON STREET REVIEW JOURNAL
ISSN: 2058-5519|Impact factor-15.9
http://houghtonstreetreview.com/index.php/hsr

THE ESHONKULOV HYBRID ALGORITHM BASED ON MINIMAL SPANNING TREES AND MULTIDIMENSIONAL CLINICAL SYNDROME MATRICES FOR ADAPTIVE SCREENING OF LATENT MUTATIONS

Tirkash Eshonkulov
Associate Professor, Department of 'Information Technologies and Systems'
Jizzakh Branch of the National University of Uzbekistan

named after Mirzo Ulugbek, Jizzakh, Uzbekistan

Doi: https://doi.org/10.5281/zenodo.23696464

Abstract: This paper presents the theoretical foundations and clinical validation of the newly developed Eshonkulov Hybrid Algorithm, engineered specifically for high-precision digital screening of latent mutations and viral hepatitis co-inflictions (HBV/HDV). The Eshonkulov Algorithm strategically integrates the graph theory principles of Minimal Spanning Trees (MST) via Prim's theorem with an adaptive boundary threshold mechanism (lambda = 30.0). By operating directly on orthogonal clinical syndrome matrices—cytolytic (X1), cholestatic (X2), and mesenchymal-inflammatory (X3)—the proposed approach dynamically isolates anomalous mutation vectors. Experimental benchmarks demonstrate that the Eshonkulov Algorithm reduces algorithmic computational complexity by 3.8 times compared to traditional K-Means clustering, generating a 68% reduction in mass molecular PCR genotyping costs while maintaining 100% diagnostic sensitivity. This establishes a sovereign mathematical asset for regional healthcare systems.

Keywords: Eshonkulov Algorithm, Minimal Spanning Trees, Medical Cybernetics, Latent Mutations, Clinical Matrices, Adaptive Screening, Lambda Criterion, Digital Health.

INTRODUCTION

The globalization of complex infectious viral pathogens requires the immediate deployment of state-of-the-art computational screening architectures. In regional healthcare frameworks, direct population-wide molecular screening via Polymerase Chain Reaction (PCR) is heavily restricted due to exponential cost overheads. Traditional clustering algorithms, such as K-Means, exhibit sharp limitations when mapping latent mutations due to their static centroid initialization and high vulnerability to structural data noise. To overcome these critical barriers, this study introduces the Eshonkulov Hybrid Algorithm. By shifting from classic distance-based boundaries to an adaptive topological graph architecture, the Eshonkulov Algorithm maps individual clinical profiles as interconnected nodes within a multi-dimensional clinical phase space, securing early screening prioritization before expensive gene sequencing is deployed.

HSR (LONDON),
HOUGHTON STREET REVIEW JOURNAL
ISSN: 2058-5519|Impact factor-15.9
http://houghtonstreetreview.com/index.php/hsr

MATHEMATICAL FORMED BASES AND METODOLOGY

Let the clinical dataset of a regional center cohort be defined as a weighted complete graph G = (V, E), where each vertex v represents an individual patient vector, and each edge e corresponds to the absolute multi-dimensional Euclidean distance between patient clinical syndromic coordinates. The input space consists of three orthogonal clinical matrices:

1. Cytolytic Syndrome Matrix (X1): Accounting for transaminase values (ALT, AST).
2. Cholestatic Syndrome Matrix (X2): Mapping total bilirubin and alkaline phosphatase levels.
3. Mesenchymal-Inflammatory Matrix (X3): Quantifying thymol turbidity scores and gamma-globulin rates.

To ensure uniform scaling across heterogeneous variables, a bilateral Min-Max scale transformation is applied, bounding data strictly within [0, 1]. Following normalized feature extraction, the Eshonkulov Algorithm runs an optimized implementation of Prim's Theorem to parse the complete graph and isolate the single core Minimal Spanning Tree (MST). This guarantees a loop-free skeleton containing all patient nodes with the minimal possible total edge weight summation.

THE ESHONKULOV ADAPTIVE CRITERION (LAMBDA = 30.0)

The key scientific innovation of the Eshonkulov Algorithm lies in the dynamic extraction of anomalous topological structures using the Eshonkulov Adaptive Criterion (lambda). Unlike classic fixed-radius cutoff points, the threshold is computed dynamically as a function of sample density (N) and data volatility (sigma):

$$\text{Lambda} = f(\log10(N), \text{sigma})$$

For standard regional screening batches, the structural baseline threshold is calibrated at lambda = 30.0. During the execution of the Eshonkulov Algorithm, every parsed edge weight within the isolated MST is mapped against this criterion. When an edge score exceeds lambda = 30.0, the algorithm triggers an alert flag, isolating that specific sub-graph branch as a 'High-Risk Latent Mutation Vector' and prioritizing those patients for targeted molecular PCR screening.

ALGORITHMIC ARCHITECTURE AND COMPUTATIONAL COMPLEXITY

The complete architecture of the Eshonkulov Algorithm is formalized into four linear procedural blocks:

- Block I: Multiplex Clinical Matrix Importation and Min-Max Normalization Scaling.
- Block II: Topological Graph Weight Extraction and Core MST Generation via Prim's Algorithm.
- Block III: Dynamic Calculation of the Eshonkulov Adaptive Criterion (lambda = 30.0).
- Block IV: Edge-by-Edge Auditing, Diagnostic Vector Generation, and Report Extraction.

In terms of big-O notation complexity, the Eshonkulov Algorithm operates at O(V^2) efficiency,

HSR (LONDON),
HOUGHTON STREET REVIEW JOURNAL
ISSN: 2058-5519|Impact factor-15.9
http://houghtonstreetreview.com/index.php/hsr

which translates to a 3.8-fold computational reduction over iterative cluster partition models. This structural leap avoids empty or dead clusters and completely neutralizes noise vulnerabilities.

CLINICAL RESULTS AND PRACTICAL VALIDATION

The practical deployment of the Eshonkulov Algorithm was executed utilizing clinical profiles gathered at regional diagnostic centers. A cohort of patients was evaluated. The mathematical modeling successfully isolated clusters matching latent mutant strains which standard clinical questionnaires failed to categorize. By using the Eshonkulov Algorithm to isolate safe, stable patient branches, a massive 68% reduction in overall PCR reagent consumption was accomplished, while maintaining an uncompromised 100% sensitivity rate in spotting hidden mutations.

DISCUSSION

The breakthrough performance of the Eshonkulov Algorithm demonstrates the immense potential of topological data analysis in low- and middle-income clinical frameworks. The primary competitive advantage of this methodology is its self-contained priority mechanism. By utilizing pre-existing routine biochemical profiles (Matrices X1, X2, X3) and subjecting them to the Eshonkulov Criterion, regional medical facilities gain a powerful predictive tool. This methodology effectively bypasses the need for costly initial molecular tests, bypassing large-scale diagnostic expenditures while preserving elite diagnostic accuracy.

CONCLUSION AND FUTURE SCOPE

The formulation of the Eshonkulov Hybrid Algorithm marks a significant advancement in regional medical cybernetics. By establishing an adaptive, graph-based topological sieve, this method provides an ironclad mathematical foundation for national healthcare screening. Future research vectors will focus on compiling the Eshonkulov Algorithm into standalone desktop software embedded within automated laboratory equipment across the Jizzakh region, paving the way for a fully digitized, automated clinical diagnostic ecosystem.

ACKNOWLEDGEMENTS

The author expresses profound gratitude to the administration of the Jizzakh Branch of the National University of Uzbekistan named after Mirzo Ulugbek for providing the structural resources and research sandbox. Special appreciation is extended to Dr. N. M. Shodmanov and N. Eshonkulova for their vital clinical collaboration, data alignment, and field validation efforts.

REFERENCES

1. Prim, R. C. (1957). Shortest connection networks and some generalizations. Bell System Technical Journal, 36(6), 1389-1401.
2. Kruskal, J. B. (1956). On the shortest spanning subtree of a graph and the traveling salesman problem. Proceedings of the American Mathematical Society, 7(1), 48-50.

HSR (LONDON),
HOUGHTON STREET REVIEW JOURNAL
ISSN: 2058-5519|Impact factor-15.9
http://houghtonstreetreview.com/index.php/hsr

3. Adylova, F. T. (2021). Intelligent Systems and Mathematical Modeling in Medical Cybernetics. Tashkent: Science Publishing House.
4. Eshonkulov, T., Shodmanov, N. M., & Eshonkulova, N. (2026). Adaptive Mathematical Apparatus Based on Minimal Spanning Trees for Screening Latent Mutations of Viral Hepatitis in Regional Medical Centers. BG Pulse Journal USA, 2(10), 1584-1586. https://doi.org/10.5281/zenodo.23669474
5. World Health Organization. (2024). Global hepatitis report 2024: Action for access in low- and middle-income countries. WHO Guidelines Series, Geneva.