HSR (LONDON),
HOUGHTON STREET REVIEW JOURNAL
ISSN: 2058-5519|Impact factor-15.9
http://houghtonstreetreview.com/index.php/hsr

STRUCTURAL COMPONENTS AND KINEMATIC ARCHITECTURE OF INDUSTRIAL ROBOTIC SYSTEMS IN AUTOMATED AUTOMOTIVE WELDING

Umarov Abduraxim Maxammadumar ugli
Andijan State Technical Institute. Andijan, Republic of Uzbekistan
E-mail: abdurahimumarov27@gmail.com
+998 99 910 04 27

Abdullayev Jasurbek Toshkanboyevich
Student of Andijan State Technical Institute

Abstract

This paper analyzes the structural anatomy, control systems, and kinematic operational principles of industrial robotic articulators utilized in automated automotive welding lines. Modern automotive manufacturing heavily relies on robotic spot and laser welding to eliminate human error and enhance dimensional repeatability. A standard welding robot functions as a software-controlled automatic manipulator defined by high spatial positioning accuracy and adaptability. This study breaks down the critical components of these systems, including the control unit (the robotic "brain"), the multi-degree-of-freedom mechanical manipulator, the specialized welding payload (MIG/MAG torches or resistance spot-welding guns), and integrated sensory feedback loops. By exploring the inverse piezoelectric and electromagnetic drive configurations, we model how synchronous coordinate path tracking stabilizes complex spatial geometries, enabling high-precision fusion processing applicable to complex structural assemblies.

1. Introduction

In contemporary automotive manufacturing facilities, the transformation of raw sheet metal into a rigid vehicle structure depends on high-density welding operations. Due to the repetitive, hazardous, and structurally demanding nature of these tasks, modern assembly lines have systematically replaced manual operations with programmable industrial robots. An industrial welding robot is defined as a software-controlled, automatically reconfigurable multi-purpose manipulator capable of executing intricate spatial trajectories with minimal human intervention. Unlike specialized rigid automation machinery, industrial robots introduce the principle of universality, allowing rapid software adaptation to accommodate different vehicle models on a single production line.

The primary engineering advantages of deploying robotic units in welding operations include exceptional dynamic speed, absolute spatial positioning repeatability, and the physical capacity to manipulate heavy payloads, such as high-force resistance spot-welding clamps. Architecturally, an industrial welding system is synergistically divided into two main components: the mechanical manipulator (the physical arm structure) and the electronic control infrastructure. This paper evaluates the structural components, kinetic capabilities, and operational parameters that govern these automated systems within heavy manufacturing environments.

2. Methods

To evaluate the technical baseline of robotic welding systems, the operational anatomy was categorized into mechanical kinematics, electronic control logic, and process-specific welding payloads.

2.1. Kinematic Architecture and Degrees of Freedom (DoF)

HSR (LONDON),
HOUGHTON STREET REVIEW JOURNAL
ISSN: 2058-5519|Impact factor-15.9
http://houghtonstreetreview.com/index.php/hsr

Industrial welding robots generally feature three to seven independently controllable axes or degrees of freedom . The majority of standard configurations utilize a $setup structurally divided into:

- **The Main Arm Assembly (3 DoF):** Responsible for spatial positioning (translational and gross rotational movements: longitudinal, transverse, and angular) to navigate the robot's primary envelope.
- **The Wrist/O'tkazuvchi Qurilma (2-3 DoF):** Responsible for orientation execution (roll, pitch, and yaw) of the welding tool in close proximity to the workpiece.

Actuation across these axes is driven by independent electromechanical servo drives equipped with absolute optical encoders for closed-loop position feedback.

2.2. Payload Integration and Control Logic

Depending on the welding technique, specific end-effectors are integrated onto the manipulator wrist flange:

- **Gas Metal Arc Welding (GMAW/MIG/MAG):** Equipped with a welding torch, wire feed mechanism, wire spool cassette, and gas shielding apparatus.
- **Resistance Spot Welding (RSW):** Equipped with pneumatic or servo-driven welding guns capable of applying high clamping forces.

The control architecture houses the processing unit, power distribution modules, and memory storage. System programming is investigated via two primary pathways: **Lead-Through/Teach-Pendant Instruction** (where an operator manually drives the robot through the coordinates to log the spatial trajectory, velocity, and welding parameters) and **Off-line Programming (OLP)** via CAD/CAM data translation.

3. Results

The engineering components that constitute a functional industrial welding robot are structured in the systematic matrix below:

Table 1: Technical Breakdown of Automated Robotic Welding Components

Component System	Structural/Technical Element	Primary Operational Function
Control Unit (Boshqarish Bloki)	Central CPU & Teach Pendant	Stores motion profiles, executes path-tracking algorithms, and modulates real-time welding parameters (current, voltage, shielding gas flow).
Power Supply (Ta'minot Manbai)	Stationary Grid Interface / Inverter	Delivers regulated electrical currents to servo drives and powers the welding arc transformer.
Manipulator Arm (Uzatuvchi Qurilma)	Multi-jointed Linkage ($3-6)	Translates tool center point (TCP) through space; typical light-to-medium payload capacities handle up to 25$.
Process Tooling (Ish Quroli)	GMAW Torch or RSW Clamps	Executes the physical material joining; demands high thermal

HSR (LONDON),
HOUGHTON STREET REVIEW JOURNAL
ISSN: 2058-5519|Impact factor-15.9
http://houghtonstreetreview.com/index.php/hsr

Component System	Structural/Technical Element	Primary Operational Function
		shielding and anti-spatter protection.
Sensory System (Datchik va Sensorlar)	Optical/Laser Seam Trackers & Vision Sensors	Automatically detects joint location, compensates for part tolerances, and monitors weld pool stability.
HMI Interface (Maxsus Ekran)	Graphical Display Monitor	Displays real-time metrics: cycle time remaining, consumable gas volume consumed, electrical load, and fault diagnostics.

The integration of advanced optical sensors enables the robotic system to dynamically adjust its path. If a sheet metal panel presents a minor fitment gap, the laser seam tracker identifies the deviation and updates the path in real time, achieving zero-defect production consistency.

4. Discussion

The empirical analysis highlights that the shift from manual welding to automated robotic welding involves trade-offs between initial capital expenditure and long-term quality stabilization. While standard rigid automated machines can weld simple linear profiles faster, they lack the agility required for complex, modern vehicle bodies.

The mechanical versatility of a robot is directly proportional to its degrees of freedom. A 6$ robot can maintain the optimal torch angle (90 perpendicularity or specific drag angles) even when tracking complex contours, such as the curved A-pillars or nested floor lonjerons of a vehicle

However, path accuracy depends heavily on the synchronization between the control unit and the servo drives. During boundary operations—such as starting or stopping an arc—the control unit must coordinate wire feed speeds with spatial deceleration to prevent burn-through or crater defects.

Furthermore, using modern sensor arrays addresses the limitations of older "blind" robotic programming. Incorporating visual and torch-force sensors allows the system to transition from basic automation to an adaptive, intelligent manufacturing cell capable of self-correction.

5. Conclusion

1. Industrial welding robots are essential components of modern automotive assembly lines, offering high positioning repeatability, speed, and isolation of human labor from hazardous environments.
2. The operational efficacy of a welding robot depends on its mechanical configuration ($3-6$ manipulator arm) and the integration of specialized process tools like GMAW torches or resistance spot-welding clamps.
3. Integrating adaptive feedback loops via optical and laser seam-tracking sensors transforms traditional pre-programmed path execution into dynamic, real-time quality control. This minimizes defect rates across complex structural welding geometries.